

PCT200i CT/PT Test System



Main Features

- Can test M/P/TP type, bushing and GIS type CT
- Ratio check up to 30 000 : 1 and 45 000 : 5
- Knee point check up to 30 000V
- Standards : IEC60044-1 /6, IEC61 869-2 , ANSI/IEEE C57.13
- Results saved in Excel format and auto assessment
- Report can be transferred to flash disk via USB port
- Weight : 1 0 kg

More than 20 CT tests can be performed automatically in one time

- Burden
- Winding resistance
- Excitation
- Polarity
- Ratio
- Ratio error and phase displacement
- Saturated inductance (Ls)
- Unsaturated inductance (Lu)
- Remanence flux (Kr)
- Secondary time constant (Ts)
- Accuracy limiting factor (ALF)
- Instrument security factor (FS)
- Transient dimensioning factor (Ktd)
- Peak instantaneous error (ϵ^{\wedge})
- Composite error
- Demagnetization

.....

Technical specifications

Output voltage range	0~120V
Output current range	0~5Arms (15A peak)
Output power	0.0001VA~500VA RMS (1500VA peak)
Ratio measurement	30000:1 or 45000:5 0.05%Typ. 0.1%Gur
Phase measurement	1min Typ. 3min Gur. 0.1min
Current measurement	range: 0~15 A (auto ranging) $\pm 0.05\%$ Typ. $\pm 0.10\%$ Gur.
Voltage measurement	range: 0~120V (auto ranging) accuracy: $\pm 0.05\%$ Typ. $\pm 0.10\%$ Gur.

Winding resistance measurement	range: 0.00 1~1 000 Ω $\pm 0.05\% \pm 1m\Omega$ Typ. $\pm 0.1\% \pm 1m\Omega$ Gur.
Burden measurement	range: 0.00 1~1 000 Ω $\pm 0.05\% \pm 1m\Omega$ Typ. $\pm 0.1\% \pm 1m\Omega$ Gur.
Communication port	USB
Dimension	470*200*245mm (WxHxL)
Weight	10 Kg
Main supply	110-240Vac/50-60Hz (nominal) 90-260Vac/45-65Hz (permissible)
Operation temperature	-10-50° C



PONOVO POWER CO., LTD.

2F,4Cell, Tower C, In.Do Mansion, No.48A Zhichun Road, Haidian District Beijing, PR China (100098)
Tel. +86 (10) 8275 5151(reception) Tel. +86 (10) 82755151ext.8887
Fax. +86 (10) 8275 5151-8103 support@relaytest.com info@relaytest.com www.relaytest.com